

## **LISTING OF THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) A method for delivering an anchor member into biological tissue comprising:

accessing and preparing an insertion site for the anchor member;

holding the anchor member at a distal end of an insertion tool;

providing the anchor member to the site with the insertion tool;

without requiring rotation of the insertion tool about a longitudinal axis of the insertion tool, causing a rotational movement of the anchor member about a first axis perpendicular to a longitudinal axis of the insertion tool whereby the anchor member engages the tissue at the site by moving about the first axis from a first position substantially aligned with the longitudinal axis to a second position at an angle relative to the longitudinal axis;

the step of causing a rotational movement of the anchor member about a first axis perpendicular to the longitudinal axis of the insertion tool comprising pushing the anchor member with a pusher member disposed concentrically in an outer tubular member of the insertion tool, the pusher member maintaining engagement with the anchor member during the step of causing the rotational movement;

wherein the anchor member is initially at least partly disposed in the outer tubular member and further comprising ejecting the anchor member using the pusher member from the outer tubular member and wherein the step of causing a rotational movement comprises using a pusher member having an angled distal surface conforming to an angled surface of the anchor member when the anchor member is at least partly in the outer tubular member; and

withdrawing the insertion tool from the site, leaving the anchor member secured at the site.

2. (Original) The method of claim 1, wherein the second position includes positions ranging from a position defined by an acute angle to the longitudinal axis to a position perpendicular to the longitudinal axis.

3. (Original) The method of claim 1, further comprising preforming a borehole at the site to receive the anchor member.

4. Canceled

5. Canceled

6. Canceled

7. (Original) The method of claim 1, further comprising disposing the pusher member and the anchor member in the outer tubular member of the insertion tool, moving the pusher member relative to the outer tubular member to eject the anchor member into a borehole in the tissue at the site with further relative movement of the pusher member causing the rotational movement.

8. (Original) The method of claim 1, further comprising after withdrawing the insertion tool, causing further rotational movement of the anchor member whereby the anchor member attains a position substantially perpendicular to the borehole.

9. (Original) The method of claim 1, further comprising applying a tug to a suture connected to the anchor member to ensure that the anchor member is secured in the borehole.

10. (Original) The method of claim 1, further comprising providing said anchor member as a rotational member having at least one cutting edge for cutting into the borehole.

11. Canceled.

12. Canceled.

13. Canceled.

14. (Currently Amended) The method of claim 1, further comprising providing the anchor member as a member ~~formed by slicing a cylinder along~~ comprising a cylinder-like member having two parallel end planes disposed at an acute angle to a longitudinal axis of the cylinder-like member, thereby forming two parallel surfaces having sharp edges.

15. (Currently Amended) A method for delivering an anchor member into biological tissue comprising:

accessing and preparing an insertion site for the anchor member;

holding the anchor member at a distal end of an insertion tool;

providing the anchor member to the site with the insertion tool;

without requiring rotation of the insertion tool about a longitudinal axis of the insertion tool, causing a rotational movement of the anchor member about a first axis perpendicular to a longitudinal axis of the insertion tool whereby the anchor member engages the tissue at the site by moving about the first axis from a first position substantially aligned with the longitudinal axis to a second position at an angle relative to the longitudinal axis;

withdrawing the insertion tool from the site, leaving the anchor member secured at the site;

further comprising providing the anchor member as a member comprising a cylinder-like member having ~~formed by slicing a cylinder along~~ two parallel end planes disposed at an acute angle to a longitudinal axis of the cylinder-like member, thereby forming two parallel surfaces having sharp edges; and

further comprising providing a looped suture about a central hub of the anchor member.

16. (Previously Presented) The method of claim 15, the step of causing a rotational movement of the anchor member about a first axis perpendicular to the longitudinal axis of the insertion tool comprising pushing the anchor member with a pusher member disposed concentrically in an outer tubular member of the insertion tool, the pusher member maintaining engagement with the anchor member during the step of causing the rotational movement; and wherein the pusher member has a rounded distal end, further comprising engaging the anchor member with the rounded distal end and causing the rotational movement.

17. (Previously Presented) The method of claim 7, wherein the pusher member has an angled surface at a distal end thereof, further comprising holding the anchor member in a fixed orientation in the outer tubular member with the angled surface prior to ejection of the anchor member from the outer tubular member.

~~19~~ 18. (Currently Amended) The method of claim 7, wherein the outer tubular member has a shoulder defining a portion of a wall of the outer tubular member of decreased thickness further comprising inserting the portion of the wall of decreased thickness into the borehole with the shoulder defining a stop for the insertion of the insertion tool into the borehole.